

## Delivery Programme Wide and Slit Coils

<u>Thickness</u>	0,10 - 8,00 mm - upon request also thinner or heavier gauge
<u>Width</u>	3,00 - 2000 mm - depending on strip thickness
<u>Coil inner diameter</u>	300/ 400/ 508 and 610 mm
<u>Coil outer diameter</u>	max. 2000 mm
<u>Coil weight</u>	about 0,5 kg/mm strip width - smaller weights upon request
<u>Finish and surface condition</u> (acc. to EN 10088-2)	<p><b>2B</b> cold rolled, heat treated, pickled, skin passed</p> <p><b>2R</b> cold rolled, bright annealed</p> <p><b>2D</b> cold rolled, heat treated, pickled (not as smooth as 2B)</p> <p><b>2H</b> work hardened, tensile strength: at your option</p> <p><b>1E</b> hot rolled, heat treated, mechanically descaled</p> <p><b>1D</b> hot rolled, heat treated, pickled</p> <p><b>1G/2G</b> ground - grit size at your option</p> <p><b>1J/2J</b> brushed or satin finish</p> <p><b>1M/2M</b> patterned, design upon request</p> <p><u>Remark:</u> First digit 1 = hot rolled First digit 2 = cold rolled</p>

**Other surfaces or conditions upon specific request.**

**All sheets/ blanks/ circles can be offered with foil and ground and/or brushed finish (pls refer to: surface treatment).**

### Edge shape

Apart from the commercial edge shapes, the versatile applications of our products require further edge shapes depending on the special requirements of our customers.

Our delivery programme responds to this request.

For further information, please refer to section "edge shape".

### Tolerances

Principally, our production is in line with DIN EN ISO 9445; closer tolerances, special executions and restrictions (i.e. special analysis) can be agreed upon.



Jenssen GmbH & Co. KG

Eisenhüttenstraße 11-17

D - 57074 Siegen - Kaan-Marienborn

Telefon 0049 (0) 271 - 77308-0

Telefax 0049 (0) 271 - 77308-11

info@jenssen-kg.de - www.jenssen-kg.de