

Delivery Programme Surface Protection

Stainless steel is more and more required to meet also aesthetic demands. Therefore, on nearly all products we can apply foil protection.

The following foil types are our standard:

Producer	Type	Colour	Thickness	Adhesion	suitable surface	Application
Novacel	4205 - PE	blue-transparent	55 µ	slight	2B, 2R, 2J	deep drawing, folding, shaping
Novacel	4105 - PE	blue-transparent	60 µ	slight	2B, 2R	deep drawing, folding, shaping
Nitto	SPV 224 - PVC	blue-transparent	70 µ	medium	2B, 2R, 2G, 2J	deep drawing, medium mechanical loading, UV-stability
Nitto	SPV 4075 . PE	blue-transparent	75 µ	medium	2B, 2R, 2J	low mechanical loading UV-stability
Novacel	4204 - PE	white with blue stripes	90 µ	medium	2B, 2R, 2G, 2J	high mechanical loading
Novacel	4213 - PE	white with blue stripes with black back	100 µ	medium	2B, 2R, 2G, 2J	high mechanical loading UV-stability
Novacel	4224 - PE	white with black back	100 µ	high	2B, 2R, 2G, 2J	high mechanical loading, suitable for laser cutting, weather proof, UV-stability

Naturally, we can supply other foils apart from the above executions. Please let us have your specific request.



Jenssen GmbH & Co. KG
Eisenhüttenstraße 11-17
D - 57074 Siegen - Kaan-Marienborn

Telefon 0049 (0) 271 - 77308-0
Telefax 0049 (0) 271 - 77308-11
info@jenssen-kg.de - www.jenssen-kg.de